

System	TH-M (Monopod) + TH-X H (Head) + TH-X H Bowl clamp + TH-M Carrying case		
Payload	4 kg / 9 lb (*1)	TH-X H	
Weight	2.7kg / 5.9 lb	Tilt+Pan angle	Tilt: +90° /-80° , Pan: 360°
Height	① H: 1890 mm W: 380 mm (※Reference)	Counterbalance	FIX
	② H: 870 mm W: 380 mm (")	Drag mode	FIX
	③ L: 865 mm (")	Temperature range	-20°C to +60°C / -4°F to +140°F
Folded length	L: 617 mm (Shortest length for carrying)	Head base	Ball \varnothing 65 mm / Flat base with 3/8" female thread
Camera plate (Sliding range)	Sliding plate (*2) \pm 30 mm / \pm 1.2"	TH-M	
Plate attachment (Screw sliding range)	1/4-20UNC screw with video pin 68 mm / 2.7"	Tilt+Pan angle	(Locked) FIX / (Unlocked) Tilt: \pm 20°, Pan: 360°
Monopod camera screw	1/4-20UNC / 3/8-16UNC	Pipe diameters	Upper: \varnothing 34 mm / middle: \varnothing 29.5 mm / Lower: \varnothing 25 mm
Pan handle	Unique pan handle (Non-telescopic)	Section	2 STAGE
		Monopod fixation	Fixing flip lock levers
		Pipe materials	Aluminum

Remarks

(*1) The monopod's maximum payload does not guarantee a monopod's free-stand position.

(*2) Available for Manfrotto and Sachtler video heads. ※ Not available for all models of Manfrotto and Sachtler.

Do not use the monopod without the free-stand base, this may cause damage to product.

Exterior Dimensions (mm)

TH-M

(Shortest length for carrying)

TH-X H

